

W504

Bright and versatile

- Installation flexibility Vertical lens shift and 1.6x zoom
- 5000 lumens, WXGA resolution
- Ultimate Control Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- Horizontal keystone and four corner adjustment

















W504

Designed for professional installation environments, the powerful high-specification W504 projector boasts a brightness of 5,000 lumens and features multiple digital connection options, with two HDMI inputs on rear and one hidden HDMI for the optional HDCast Pro dongle. For more complex installations, this projector is equipped with a large zoom range, vertical lens shift and a built-in geometric adjustment feature - ideal for uneven walls or where a projector placement is awkward and needs to be installed at an angle.

High contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.





Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles.



Integrated speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers.

Energy saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

Auto power off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto power off" feature automatically turns off the projector after a set period of time.

Eco AV mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.



Vertical lens shift

Simplify installation with vertical lens shift, which provides a wider range of projector placement possibilities. This makes it easier to position the projector in your room and enables a wider range of screen size options.

Four corner adjustment

Individually warp each corner of the image to create a perfectly square image. Ideal for image stacking, uneven walls or where projector placement is awkward and needs to be installed at an angle.

Large zoom range

A large zoom range enables multiple placement possibilities at a variety of distances from the projection screen. An advantage to this is that expensive interchangeable lens projectors can be substituted with a more cost effective solution whilst still retaining a diverse choice of positioning options.

MHL

Turn your projector into a smart display by connecting your smartphone or tablet with a single cable using MHL, enabling you to view presentations and documents, stream videos and share photos on the big screen.

Colour Guarantee

We are so confident that the image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





Give powerful presentations and educational lessons with stunning colours. Optoma projectors provide you with reliable colour performance suitable for any content and environment. From accurate sRGB colours for true life like images to vibrant punchy presentations. We have a display mode to specific meet your needs.



without

Quick resume

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

USB power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast or the Optoma WHD200 wireless HDMI device.

Networking and control

Featuring a wide range of options you can remotely control and monitor the projector.

RS232

Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage using any control system.

AMX Compatibility

Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.

LAN Control

- Using the compatible RoomView® software you can power on/off, monitor, manage and control up to 250 projectors at the same time from any computer.
- · Schedule the projectors to power on/off.
- Control and alter the projector settings using the simple web browser.
- Emergency text broadcast capabilities for urgent or important announcements.
- Automatically receive email updates for lamp maintenance.



Specification

Presiduan WXA 1280 x 800 Brightness ¹ (Bright Mode) 5000 AMSI Lumens Contrast 15,000:1 Typical lamp life ² Eco+/Dynamic/Eco/Bright 5000/4500/4000/3000 (hrs) Throw Ratio 5000 AMSI Lumens Contrast 5000/4500/4000/3000 (hrs) Throw Ratio 14.8 - 2.35 (Mist: 96.2%-112.4% Zoom Type 1.5k Manual Lens Shift +16.2% Vertical Vertical, 4.30° Horizontal Kertical Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 364 225 x 132 Aspect Ratio 16 10 Native, 16.94.3 Compatible Offset 96.2%-112.4% Projection Distance 1.3 - 9 fbm (25.66° - 301.15°) Diagonal 16:10 Projection Distance 1.3 - 9 fbm (25.66° - 301.15°) Diagonal 16:10 Projection Distance F1.3 - 26, fize.0.91-32.63mm, 1.6x Manual Zoom Uniformity 85% Compatibility UX46, XSC4, HD, WXCA, XGA, SVGA Video Compatibility Video XA, SXG4, 100, VICA, 700, 60 / Microsofte Xbox 360 are now supported as part of the HDMI v1.4a specification. <	Display Technology	Single 0.65" WXGA DLP® Technology by Texas Instruments
Brightness ¹ (Bright Mode) 5000 ANSI Lumens Contrast 15,000:1 Typical lamp life ² Eco+/Dynamic/Eco/Bright 5000/4500/4000/3000 (hrs) Throw Ratio 1.48 - 2.35, Offset: 96.2%-112.4% Zoom Type 1.5K Manual Lens Shift +16.2% Vertical I/O Connectors 3xHDMI (1.4a 3D support) + MHL, VGA (YPDP/r/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (Kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Nuice, 16:9/4:3 Compatible Offset 96.2%-112.4% Projection Screen Size 0.68 - 756m (25.66° - 301.15″) Diagonal 16:10 Projection Lens F12.5-3.26 (F20.91-32.63mm, 1.6x Manual Zoom Unformity BS Support Vide Compatibility Video Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Support Full 30 - The 3D Features of Optoma projectors can vis be used with compatible 3D content. Typical applications include use with 3D education of 3D designari modiceling systems. 3D TV broadcast systems, (SKY in the UK		
Contrast 15,000:1 Typical Lamp Mic? Ecor/Bright 5000/4500/4000/3000 (hrs) Throw Ratio 1.48 - 2.35, Offset: 96.2%-112.4% Zoom Type 1.5k Manual Lens Shift +16.2% Vertical Lens Shift +16.2% Vertical Joronnectors 33HDNI (1.4 a 3D support) + MHL, VGA (YPbP/r/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, R32, X46, UBB-A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 369 × 295 x 132 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96 2%-112.4% Projection Distance 1.3 - 9.6m Projection Distance 1.3 - 9.6m Projection Distance 1.3 - 9.6m Video Compatibility UXGA, XGA, XGA, SVGA Oright B - Maximus B - 7.65m (25.60 ⁻¹ - 301.15 ⁺) Diagonal 16:10 Projection Lens F12.5-3.26; f=20.91+-32.63mm, 1.6x Manual Zoom Uniformity B5% Compatibility UXGA, SXGA+, HD, WXGA, SVGA Support Full 30 - The 3D features of Optoma projectors can only be used with comp		5000 ANSI Lumens
Typical lamp life ² Eco+/Dynamic/Eco/Bright 5000/4500/400/2000 (hrs) Throw Ratio 1.48 - 2.36, Offset: 96.2%~112.4% Zoom Type 1.5.X Manual Lens Shift +16.2% Vertical I/O Connectors XHLDMI (1:4 a 3D support) + MHL, VGA (YPbP//RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, R5232, R146, USB-A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30' Vertical, ± 30' Horizontal Weight (Kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 161:01 Native, 16:9/4:3 Compatibile Offset 96.2%~112.4% Projection Screen Size 0.68 - 7.656 (* - 301.15?) Diagonal 16:10 Projection Distance 1.3 - 9.6m Projection Compatibility PAL SECAM 576/jb, NTSC 480/jb, HD 720/r1080/1080p Video Compatibility PAL SECAM 576/jb, NTSC 480/jb, HD 720/r1080/1080p Yideo Compatibility PAL SECAM 576/jb, NTSC 480/jb, HD 720/r1080/1080p 3D Compatibility PAL SECAM 576/jb, NTSC 480/jb, HD 720/r1080/1080p Yote Compatibility PAL SECAM 576/jb, 700.200 3D Compatibility PAL SECAM 576/jb, 700.200 3D Com		15,000:1
Drow Ratio 1.48 - 2.35, Offset: 96.2%-112.4% Zoom Type 1.5x Manual Lens Shift +16.2% Vertical I/O Connectors 3xHDMI (1.4 a 3D support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, R5232, R145, USB-A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watis) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:3/4:3 Compatible Offset 99.2% - 112.4% Projection Screen Size 0.68 - 7.5m (25.66° - 301.15°) Diagonal 16:10 Projection Istance 1.3 - 9.6m Projection Lens F12.5-3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity B5% Computer Compatibility PAL SECAM 576/p, NTSC 480/p, HD 720/1080/1080p 3D Support Full SD - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modeling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D TM and 3D games from the Sonty PF.3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Fild ED-1012 Frame-pack: 1080/p24, 720p50 / 60 Orver-Under: 1080/p24		- ,
Zoom Type 1.5x Manual Lens Shift +16.2% Vertical LO Connectors Skt/DMI (14 a 3D support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (Kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16°10 Native, 16°94/3 Compatible Offset 96.2%-112.4% Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16°10 Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16°10 Projection Lens F12.5-3.26; f=C0.91-32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/p. NTSC 480/ip, HD 720p/1800/1800p Side-by-Side: 1080/60 (60, 720, 50° of 00 Sorterns. Typical applications include use with 3D educational or 3D design and modeling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ^W and 3D games from the Sont@ PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 1080/60 (60, 720,50 / 60		
Lens Shift +16.2% Vertical I/O Connectors SxHDMI (14.a 30 support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96.2%-112.4% Projection Distance 1.3 - 9 6m Projection Distance 1.3 - 9 6m Projection Distance F/2.5-3 26; Fr20.91-32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/0, NTSC 480/p, HD 720p/1080/1080p 3D Support Fuil 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modeling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D TM and 3D games from the Soroy PS3 or Microsofte Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side-1080(50 / 60, 720,550 / 60 Horizontal Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion<		
IO Connectors 3xHDMI (1 4a 3D support) + MHL, VGA (YPDPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB- A Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:94:3 Compatible Offset 96.2%-112.4% Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16:10 Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16:10 Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16:10 Projection Lens Fi2.5-3.26; f=20.91-32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL ECAM 576/p, NTSC 480/p, HD 720/1080/1080p SD Compatibility PL ECAM 576/p, NTSC 480/p, HD 720/1080/1080p SD Compatibility PL ECAM 576/p, NTSC 480/p, HD 720/1080/1080p SD Compatibility PL ECAM 576/p, NTSC 480/p, HD 720/1080/1080p SD Compatibility PL ECAM 576/p, NTSC 480/p, HD 720/1080/1080p SD Compatibility PL ECAM 576/p, NTSC 480/p, HD 720/1080/1080p		
RS232, RJ45, USB-Å Power (1.5A), 3D-Sync, USB mouse/service Speaker (Watts) 32 Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96.2% +112.4% Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16:10 Projection Lens F/2.5-3.26, f=20.91-32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility VXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility Status of a catures of Optima projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D TM and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 108050 / 60 Veritial Scan Ra		
Keystone Correction ± 30° Vertical, ± 30° Horizontal Weight (kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96.2%-112.4% Projection Screen Size 0.68 - 7.65m (25.66° - 301.15°) Diagonal 16:10 Projection Lens Fi2.5~3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/i/p, NTSC 480/i/p, HD 720p/1080//1080p 3D Support Full 30 - The 30 Features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Songy 6PS an Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 1080150 / 60, 720p50 / 60 Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 36B Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz		RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service
Weight (kg) 4.6 Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96.2%-112.4% Projection Screen Size 0.68 - 7.65m (25.66" - 301.15") Diagonal 16:10 Projection Lens F/2.5-3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility VXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/µ, NTSC 480/µ, HD 720/1/080/1/080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720550 / 60 Vertical Scan Rate 15.375-91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Speaker (Watts)	
Dimensions (W x D x H) 369 x 295 x 132 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96:2%~112.4% Projection Screen Size 0.68 - 7.65m (25.66" - 301.15") Diagonal 16:10 Projection Lens F/2.5-3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility VXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/p, NTSC 480//p, HD 720p/1080//1080p 3D Support Full 3D - The 3D features of Optima projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ^M and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side 1008150 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)		
Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 96.2%-112.4% Projection Screen Size 0.68 - 7.65m (25.66" - 301.15") Diagonal 16:10 Projection Lens F/2.5-3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Compatibility PX Sca Aspect Aation Video Compatibility PAL SECAM C4 800/p. HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), BUL-73y 3D ^M and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-V-Side:108010/ 60, 720p50 / 60 Horizontal Scan Rate 24 ~ 85Hz (120Hz for 3D) Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Nolse Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-320W German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian Standard Accessories AC power control, 2x AA batteries, guick start card, CD user manual <td></td> <td></td>		
Offset 96.2%-112.4% Projection Distance 0.68 - 7.65m (25.66" - 301.15") Diagonal 16:10 Projection Distance 1.3 - 9.5m Projection Lens F/2.5~3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/ip, NTSC 480/ip, HD 720p/1080i/1080p 3D Support Full 30 - The 30 features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ™ and 3D games from the Song/81 or Nicrosoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080/50 / 60, 720p50 / 60 Voer-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.375-91.146 KHz Vertical Scan Rate 10.7 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)		
Projection Screen Size 0.68 – 7.65m (25.66" - 301.15") Diagonal 16:10 Projection Distance 1.3 - 9.6m Projection Lens F/2.5-3.26; f=20.91-32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/ip, NTSC 480/ip, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D TM and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.375-91.146 KHz Vertical Scan Rate 107 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Aspect Ratio	16:10 Native, 16:9/4:3 Compatible
Projection Distance 1.3 - 9.6m Projection Lens F/2.5~3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.375~91.146 KHz Vertical Scan Rate 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Offset	
Projection Lens F/2.5~3.26; f=20.91~32.63mm, 1.6x Manual Zoom Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 00, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Vertical Scan Rate 15.375~91.146 KHz Vertical Scan Rate 15.375~91.146 KHz Vertical Scan Rate 10.7 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Projection Screen Size	0.68 – 7.65m (25.66" - 301.15") Diagonal 16:10
Uniformity 85% Computer Compatibility UXGA, SXGA+, HD, WXGA, SVGA Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Farme-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Horizontal Scan Rate 16.375-91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Projection Distance	1.3 - 9.6m
Computer Compatibility UXGA, SXGA+, HD, WXGA, XGA, SVGA Video Compatibility PAL SECAM 576/p, NTSC 480//p, HD 720p/1080/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.375-91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Projection Lens	F/2.5~3.26; f=20.91~32.63mm, 1.6x Manual Zoom
Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems. (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Vertical Scan Rate 15.375-91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Uniformity	85%
3D Support Full 3D - The 3D features of Optima projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Forizontal Scan Rate 15.375-91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Computer Compatibility	UXGA, SXGA+, HD, WXGA, XGA, SVGA
use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.375~91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p
3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Vertical Scan Rate 15.375~91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	3D Support	use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™
Horizontal Scan Rate 15.375~91.146 KHz Vertical Scan Rate 24 ~ 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	3D Compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60
Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Horizontal Scan Rate	15.375~91.146 KHz
Displayable Colours 1.07 Billion Noise Level (Eco mode) 30dB Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Vertical Scan Rate	24 ~ 85Hz (120Hz for 3D)
Power Supply 100-240V, 50-60Hz Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Displayable Colours	
Power Consumption 365W Bright mode / 287W Eco+ mode (<0.5W Standby)	Noise Level (Eco mode)	30dB
Lamp Type 310W Security Kensington Lock, Password Protection On Screen Display 19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish,Greek, Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian Standard Accessories AC power cord, remote control, 2x AA batteries, quick start card, CD user manual Optional Accessories Wireless 3D system, Wireless 3D glasses, DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes RoHS Compliant	Power Supply	100-240V, 50-60Hz
Security Kensington Lock, Password Protection On Screen Display 19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish,Greek, Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian Standard Accessories AC power cord, remote control, 2x AA batteries, quick start card, CD user manual Optional Accessories Wireless 3D system, Wireless 3D glasses, DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes RoHS Compliant	Power Consumption	365W Bright mode / 287W Eco+ mode (<0.5W Standby)
On Screen Display 19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish,Greek, Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian Standard Accessories AC power cord, remote control, 2x AA batteries, quick start card, CD user manual Optional Accessories Wireless 3D system, Wireless 3D glasses, DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes RoHS Compliant	Lamp Type	
On Screen Display 19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish,Greek, Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian Standard Accessories AC power cord, remote control, 2x AA batteries, quick start card, CD user manual Optional Accessories Wireless 3D system, Wireless 3D glasses, DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes RoHS Compliant	Security	Kensington Lock, Password Protection
Optional Accessories Wireless 3D system, Wireless 3D glasses, DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes RoHS Compliant	On Screen Display	19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek,
Optional Wireless Yes RoHS Compliant		
RoHS Compliant		
		Yes
Colour Guarantee 5 Years	RoHS	Compliant
	Colour Guarantee	5 Years



Optoma Europe Ltd. 1 Bourne End Mills, Hemel Hempstead, Hertfordshire HP1 2UJ, UK www.optoma.co.uk

Brightness and lamp lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions. Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. Copyright © 2015, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Crestron®, the Crestron and RoomView® logo are registered trademarks of Crestron Electronics, Inc. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. Some images may be simulated. Copyright © 2018, Optoma Europe Limited. Optoma, NuForce and Nu are registered trademarks of Optoma Corporation. Optoma Europe Limited is the licensee of the registered trademarks. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP® DrilliantColor™ and the DLP logo are registered trademarks of excepted, all specifications are are subject to change without use Drift Drift Drift Drift and the DLP logo are registered trademarks of identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions

excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images are for representation purposes only and may be simulated. All content on this site is protected by copyright.

Privacy Terms and conditions

Registered Office: 1 Bourne End Mills, Hemel Hempstead, Hertfordshire HP1 2UJ, UK . Registered No. 3399395

22/06/2018 17.48